

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 August 2005 (18.08.2005)


PCT

(10) International Publication Number
WO 2005/076254 A1

- (51) International Patent Classification⁷: **G09G 3/32**
- (21) International Application Number:
PCT/IB2005/050154
- (22) International Filing Date: 13 January 2005 (13.01.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0401035.1 17 January 2004 (17.01.2004) GB
- (71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **FISH, David, A.** [GB/GB]; c/o Philips Intellectual Property, & Standards, Cross Oak Lane, Redhill Surrey RH1 5HA (GB).
- (74) Agents: **WILLIAMSON, Paul, L.** et al.; c/o Philips Intellectual Property, & Standards, Cross Oak Lane, Redhill Surrey RH1 5HA (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: ACTIVE MATRIX DISPLAY DEVICES



(57) Abstract: An active matrix display device stores a transistor drive voltage on a storage capacitor (24; Cs). A light-dependent device (27) effects discharge of the storage capacitor in dependence on the light output of the light emitting display element (2). Power is provided to each pixel from a first power line (26), and one of the light dependent device and the storage capacitor is coupled to a second power supply line (50), to which a varying voltage is provided during a pixel illumination period. By varying the voltage on one of the power supply lines, the discharge characteristics of the capacitor by the optical feedback system are altered to provide compensation for the light-dependent device leakage currents.